

# PX3-100 MP2



## Multipurpose Lithium Grease

High Performance

### Description:

**PX3-100 MP2** is a mineral oil based Lithium grease fortified with, **anti-wear**, **anti-oxidation** and **anti-corrosion** additives. This high performance grease is suitable for wide range of industrial and automotive applications.

### Performance & Features:


- Good high temperature performance up to **130°C**
- Good oxidation resistance
- Excellent wear and corrosion protection
- Long storage life
- Good mechanical stability
- Equivalent to SHELL GADUS S2 V100 2 & SKF LGMT 2

### Typical Applications:

- Electric motor bearing
- Automotive wheel bearing
- Agricultural equipment
- Water pump bearing
- Conveyors
- Industrial fans

### Properties:

Specifications	Methods	Conditions	Unit	PX3-100 MP2
Base oil type				Mineral oil
Base oil viscosity @ 40 °C	ASTM D 445		cSt (mm <sup>2</sup> /s)	100
Thickener type				Lithium Soap
Dropping point	ASTM D566		°C	>185
NLGI Consistency			NLGI- class	<b>2</b>
Worked penetration	ASTM D217	60 Dh	mm/10	265 – 295
Operating Temperature Range				-20 °C to + 130 °C
Colour				Brown



Golestan Street. No 55.  
Parandak Industrial  
Town: Iran



+98 912 5343 599  
+98 919 4365 681  
+98 86 4528 3020



[www.px3lube.com](http://www.px3lube.com)  
[info@px3lube.com](mailto:info@px3lube.com)